

Zebra® Z Series®



The ZM400™ and ZM600™ printers fulfil all of the functions of the current Z Series range, only better: more connectivity choices, improved performance and easier maintenance make the enhanced Z Series ideal for a wide range of applications.

Better connected for a connected world

- The ZM400 and ZM600 provide enhanced connectivity via USB 2.0, secure 802.11b/g wireless, or the new ZebraNet® 10/100 Print Server that allows simultaneous use of parallel and network connections
- A choice of print resolutions including 200-, 300- and 600dpi, XML-enabled printing and RFID-ready investment protection allows the ZM400 and ZM600 printers to integrate into a wide variety of applications
- These enhanced Z Series printers provide improved usability with easy loading of ribbons and labels, simple setup via a large LCD display and simple maintenance of printheads and platens

KEY FEATURES

- Improved 10/100 Ethernet
- Secure 802.11b/g wireless
- User interface supporting Asian languages
- Choice of 200-, 300- and 600dpi print resolutions

IDEAL FOR:

- ✓ Work in progress
- ✓ Order fulfilment
- ✓ Compliance labelling
- ✓ Distribution
- ✓ Warehouse management
- ✓ Shipping/receiving
- ✓ Post and parcel

Get the most out of your Zebra, put Genuine Zebra Supplies™ in!

Zebra offers a wide range of supplies for Z Series printers, all made to a high standard and suitable for a variety of applications.

- Manufactured exclusively for Zebra printers
- Laboratory-tested for optimum performance
- Proven to minimise wear and tear on printheads



▶ For more information, visit www.zebra.com

SPECIFICATIONS AT A GLANCE*

STANDARD FEATURES

- Print methods: Thermal transfer or direct thermal
- Construction: Die-cast aluminium base, frame and printhead mechanism
- Metal media cover with large clear window
- Element Energy Equalizer™ (E³) for superior print quality
- Auto-calibration
- Real-time clock
- Auto-ranging (90–265VAC) power supply
- Colour-coded operator cues
- Multi-language control panel with back-lit 240x128 pixel display

PRINTER SPECIFICATIONS

Resolution

- 8 dots per mm/203dpi; 12 dots per mm/300dpi; 24 dots per mm/600dpi (ZM400 only)

Memory

- Standard: 8MB flash, 16MB DRAM
- Optional: Factory-installed 64MB flash

Print width

- ZM400: 104mm/4.09"
- ZM600: 168mm/6.6"

Print length

- ZM400: with 203dpi: 3,988mm/157"; with 300dpi: 1,854mm/73"; with 600dpi: 991mm/39"
- ZM600: with 203dpi: 2,590mm/102"; with 300dpi: 1,143mm/45"

Print speed

- 203dpi: 254mm/10" per second
- 300dpi: 203mm/8" per second
- 600dpi: 102mm/4" per second

Media sensors

- Fixed reflective sensor
- Adjustable transmissive sensor

MEDIA CHARACTERISTICS

Maximum label and liner length

- Maximum non-continuous: 991mm/39"

Maximum label and liner width

- ZM400 – 114mm/4.5"
- ZM600 – 178mm/7.0"

Maximum roll diameter

- 203mm/8.0"

Core diameter

- 76mm/3"

Media thickness

- 0.058mm/0.0023" to 0.25 mm/0.010"

Media types

- Continuous, die-cut, tags, black-mark
- For optimum print quality and performance, use Genuine Zebra Supplies

RIBBON CHARACTERISTICS

Outside diameter

- 81.3mm/3.2"

Standard length

- 300m/984' or 450m/1,476'

Ratio

- 3:1 media-roll to ribbon. Ribbon must be at least as wide as media

Width

- ZM400: 51mm/2.00" to 110mm/4.33"
- ZM600: 51mm/2.00" to 174mm/6.85"

Ribbon setup

- Ribbon wound ink-side out (ribbon wound ink-side in can be used with optional ribbon spindle)

Core internal diameter

- 25.4mm/1.0"

OPERATING CHARACTERISTICS

Environmental

- Operating temperature: 0°C to 40°C (Direct Thermal); 5°C to 40°C (Thermal Transfer)
- Storage temperature: -40°C to 60°C
- Operating humidity: 20–85% non-condensing
- Storage humidity: 5–85% non-condensing

Electrical

- Universal auto-ranging (PFC-compliant) power supply 90–265VAC; 48–62Hz

Agency Approvals

- IEC60950-1, EN 55024, EN 61000-3-2, EN 61000-3-3, EN 55022 Class B
- Markings: cTUVus, CE, FCC-B, ICES-003, VCCI, C-Tick, NOM, CCC, GOST-R, BSMI, S-Mark (Arg), SABS, MIC, ZIK

PHYSICAL CHARACTERISTICS

Width

- ZM400: 278mm/10.9"
- ZM600: 341mm/13.4"

Height

- ZM400: 338mm/13.3"
- ZM600: 338mm/13.3"

Depth

- ZM400: 475mm/18.7"
- ZM600: 475mm/18.7"

Weight

- ZM400: 15kg/32.4lb
- ZM600: 16kg/34.7lb

Shipping weight

- ZM600: 22kg/49lb
- ZM400: 24.5kg/54lb

ZEBRALINK™ SOLUTIONS

Software

- ZebraDesigner™ Pro
- ZebraDesigner for XML
- ZebraNet™ Bridge Enterprise

- ZebraNet Utilities v 7.0
- Zebra Universal Driver
- Additional scalable and bitmapped fonts available

Networking/Connectivity

- ZebraNet Wireless Plus
- ZebraNet 10/100 Print Server
- ZebraNet PrintServer II
- RS-232-C serial port
- High-speed IEEE 1284 bi-directional parallel interface
- USB 2.0

Firmware

- ZPL II®
- EPL™
- XML-enabled printing
- APL™
- Web View
- Alert

FONTS/GRAPHICS/SYMBOLOLOGIES

Fonts and character sets

- 7 bitmapped, 1 smooth-scalable
- Native open type font support
- Global printing – Unicode™-compliant for fast multi-language on-demand thermal printing right out of the box
- Contains UFST® from Monotype Imaging Inc.

Graphic features

- Supports user-defined fonts and graphics, including custom logos
- ZPL II drawing commands for boxes and lines

Bar code symbologies

- Linear Bar Codes: Codabar, Code 11, Code 16k, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case C Codes, EAN-8, EAN-13, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Planet Code, Plessey, Postnet, Standard 2-of-5, UPC-A, UPC-E, UPC and EAN 2 or 5 digit extensions
- Two-Dimensional: Aztec, Codablock, Code 49, Data Matrix, GS1 DataBar (RSS), MaxiCode, MicroPDF417, PDF417, QR Code, TLC 39

OPTIONS AND ACCESSORIES

- Factory-installed 64MB flash memory option
- Cutter with catch tray
- Peel – a front-mount, passive-peel option with no liner take-up
- Liner take-up (works with peel option) – full-roll liner take-up spindle (fits standard base, ZM400 only)
- Rewind – internally rewinds full label roll on 3" (76mm) core (comes with taller, non-standard printer base)
- RS-422/RS-485 serial port adaptor
- Optional ribbon spindle to support ribbon wound ink-side in (ZM400 only)

*Specifications subject to change without notice.

© 2007 ZIH Corp. APL, Element Energy Equalizer, EPL, Genuine Zebra Supplies, ZebraDesigner, ZebraLink, ZebraNet and all product names and numbers are Zebra trademarks, and E³, Z Series, Zebra, representation of Zebra Head, ZebraNet and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Unicode is a trademark of Unicode, Inc. UFST is a registered trademark of Monotype Imaging, Inc. All other trademarks are the property of their respective owners.

Thinking about mobilising your workforce?

The use of mobile printers in a warehouse or supply-chain environment improves productivity and provides a fast return on investment.

- ▶ To find out how your business could benefit from a Zebra mobile-printing solution, please visit www.zebra.com, call +44 (0)1494 472872 or e-mail mseurope@zebra.com



Zebra Technologies – EMEA Headquarters

Zebra Technologies Europe Limited, Zebra House, The Valley Centre, Gordon Road, High Wycombe, Buckinghamshire HP13 6EQ, UK
Tel: +44 (0)1494 472872 Fax: +44 (0)1494 768251 E-mail: mseurope@zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East & Africa: Dubai, India, South Africa